



NOTES:

1. PRECAST SECTIONS TO BE JOINED WITH TONGUE AND GROOVE JOINTS SEALED WITH MASTIC TYPE BITUMINOUS JOINTING COMPOUND.
2. PRECAST CONCRETE BARREL SECTION ASTM C-478 AND ASTM C-443.
3. PRECAST CONCRETE RING CONSTRUCTION ASTM C-478-64T ADJUSTMENT TO 12" MAXIMUM, USING THE MINIMUM NEEDED TO ACHIEVE THE DESIRED ELEVATION WITH 3 RINGS MAXIMUM. RUBBER NOISE RINGS SHALL BE USED IN ALL TRAFFIC AREAS.
4. STEPS SHALL BE EMBEDDED INTO WALL A MINIMUM OF 3" AND SHALL NOT BE EXTENDED ON THE OUTSIDE.
5. MINIMUM DIAMETER (D) SHALL BE 48" UNLESS OTHERWISE NOTED ON THE PLAN.
6. A FACTORY INSTALLED "RUBBER BOOT SEAL" SHALL BE PRECAST INTO ALL PIPE OPENINGS WHEN CATCH BASINS ARE TIED INTO COMBINED SEWER SYSTEM.

Village of Mount Prospect	
Public Works Department	
1700 W Central Rd	
CATCH BASIN W/ RESTRICTOR DETAIL	
Scale: None	Last Revised: 05-09