



Village of Mount Prospect

Community Development Department – Building Division
50 South Emerson Street
Mount Prospect, Illinois 60056
Phone: 847/870-5675 Fax: 847/870-6620 TDD: 392-6064

SEWER LINING CHECKLIST AND CONDITIONS

Sewer Lining Checklist and Conditions

- It is the responsibility of the plumbing contractor and licensed plumber to adhere to all Illinois State Plumbing Code requirements.
- By accepting these conditions, the permit applicant, property owner, and all contractors on said permit agree to hold the Village and its employees harmless for any consequential issues that arise or failure of said installation of lining product with repairs. It is not encouraged or recommended to line private lines if there is any deterioration or spot/complete repair required at the private sewer lateral. Lining of a sewer line is unnecessary if the existing line is repaired and flows properly.
- Prior to any work starting, the Public Works Department and Community Development Department must review the permit application for sewer lining, which may take up to 22-30 days for review. It is the responsibility of the plumber to make temporary repairs, rod, or jet the sewer to maintain the line flowing for occupancy of the structure.
- When televising the existing line and after liner installation, aim the camera at the front of the structure and the address number so that it may be recorded on the video.
- **You must submit:**
 - One (1) copy of all product data submitted for approval, including installation instructions
 - One (1) copy of the MSDS sheet(s) from the product manufacturer submitted for approval
 - One (1) copy of the manufacturer's data sheet on the liner lubricant (lubricant must be bio-degradable and non-toxic)
 - One (1) **video in DVD format or by email via YouTube link to building@mountprospect.org**, of the current conditions of the sewer service lateral, including connection to the main (picture quality must be clear and the footage at a slow enough rate to allow for proper inspection).
- **Spot repairs must be performed when/if:**
 - Sewers have a joint misalignment of more than one-half (1/2) inch
 - Sewers are missing pieces of the tile in the flowline
 - Sewers have settled and are holding water
 - Sewers have an elongation of the tile diameter
- You must also submit One (1) **video in DVD format or by email via YouTube link to building@mountprospect.org**, of the post liner installation of both the service lateral and the Village sewer main at the service opening (picture quality must be clear and the footage at a slow enough rate to allow for proper inspection). Liner must not protrude into the main sewer.