



Village of Mount Prospect
Community Development Department
50 S. Emerson Street
Mount Prospect, Illinois 60056
Phone: (847) 870-5675

Email: building@mountprospect.org

Shed Supplement

PERMIT SUBMITTAL REQUIREMENTS

- Submit 3 copies of the following:
 1. Current plat of survey with location of shed clearly illustrated and setback information noted.
 2. Elevation plan clearly illustrating the material, height, and roof pitch.

- Schedule a final inspection. Failure to comply can result in a hold being placed on your real estate transfer stamp and in fines up to \$1,500 per issue of non-compliance (Sec. 21.403, Chapter 14).

RESIDENTIAL SHED REGULATIONS (Sec. 14.306, Chapter 14)

A permit may be granted only if the proposed shed is in compliance with the provisions of the Village Code. Please refer to the Village Code for the complete regulations. The following provides a brief overview.

Area


- A shed may be no larger than either 2% of the lot area or 200 square feet, whichever is smaller.

Roof Pitch

- A minimum of 3:12 roof pitch is required.

Height

- The maximum height permitted for a shed is 10' as measured from the finished grade to the roof peak. (See diagram below)





Village of Mount Prospect
Community Development Department
50 S. Emerson Street
Mount Prospect, Illinois 60056
Phone: (847) 870-5675

Email: building@mountprospect.org

Shed Supplement

Location

- A minimum of 3' separation from the principal structure is required.
- Sheds are not permitted in front yards or exterior side yards.
- Sheds may be installed in the rear and interior side yards, provided the following setbacks are met:
 - On lots 55' in width or less, sheds must be set back 3' from any interior side or rear lotline.
 - On lots greater than 55' in width, sheds must be set back 5' from any interior side or rear lot line.
- A shed may not be placed on any Village utility or easement.
- A shed may not be utilized to store motor vehicles or as office, work, or living space. The storage of household items, equipment necessary to maintain the primary structure and surrounding property, and small recreational equipment is permitted.

Base and Anchorage

- Prefabricated sheds shall be constructed upon a moisture and vermin resistant as provided or specified by the manufacturer. In addition, the shed and base shall be anchored to the ground using helical anchors or other methods as approved by the manufacturer.
- Custom or hand built sheds shall be constructed on a 4" minimum thickness concrete slab, poured over a 4" minimum thickness compacted stone base. ½" steel anchors at 6'-0" on center maximum and within 1'-0" of all base plate ends shall be used to anchor the shed to the concrete base.